# Sprayway<sub>®</sub>

# SAFETY DATA SHEET

#### 1. Identification

Product identifier SW248 FRESH TOTAL RELEASE BLAST OUT

Other means of identification

Product code 1000014034

Recommended use Air Freshener

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company nameSprayway, Inc.Address1000 INTEGRAM DR

Pacific, MO 63069 United States

**Telephone** 1-630-628-3000

E-mail orders@spraywayinc.com

**Emergency phone number** Emergency - US 1-866-836-8855

Emergency - Outside US 1-952-852-4646

Supplier Not available.

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSerious eye damage/eye irritationCategory 2A

Specific target organ toxicity, single exposure Category 3 narcotic effects

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness.

**Precautionary statement** 

**Prevention** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated

area. Wear eye protection/face protection.

Response IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER/doctor if you feel unwell. If eye irritation persists: Get

medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

**Supplemental information** None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	<u>%</u>
Acetone		67-64-1	60 - 100
Butane		106-97-8 10 - 3	

Chemical name	Common name and synonyms	CAS number	%
Propane		74-98-6	10 - 30
Other components below	reportable levels		3 - 7

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON Inhalation CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth.

Ingestion

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Most important

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. symptoms/effects, acute and delayed

Indication of immediate Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. medical attention and special treatment needed

Ensure that medical personnel are aware of the material(s) involved, and take precautions to **General information** protect themselves.

# 5. Fire-fighting measures

Alcohol resistant foam. Powder. Carbon dioxide (CO2). Suitable extinguishing media

Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media

Contents under pressure. Pressurized container may explode when exposed to heat or flame. Specific hazards arising from During fire, gases hazardous to health may be formed. the chemical

Firefighters must use standard protective equipment including flame retardant coat, helmet with Special protective equipment

and precautions for firefighters face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Move containers from fire area if you can do so without risk. Containers should be cooled with Fire fighting

water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose equipment/instructions holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

General fire hazards Extremely flammable aerosol.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground. **Environmental precautions** 

# 7. Handling and storage

#### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing gas. Avoid contact with eyes. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

# Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Type

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

Value

# 8. Exposure controls/personal protection

#### Occupational exposure limits

Components

US. ACGIH	<b>Threshold</b>	<b>Limit Values</b>
-----------	------------------	---------------------

Acetone (CAS 67-64-1)	STEL	500 ppm
•	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Canada. Alberta OELs (Occupation	onal Health & Safety Code. Sch	nedule 1. Table 2)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	1800 mg/m3
		750 ppm
	TWA	1200 mg/m3
		500 ppm
Butane (CAS 106-97-8)	TWA	1000 ppm
Propane (CAS 74-98-6)	TWA	1000 ppm
		s for Chemical Substances, Occupational Health and
Safety Regulation 296/97, as ame Components	ended) Type	Value
Acetone (CAS 67-64-1)	STEL	500 ppm
Acetone (OAO 07-04-1)	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	750 ppm
Butane (end 100 or o)	TWA	600 ppm
Canada Manitaha OELa (Dag. 21		• •
Canada. Manitoba OELs (Reg. 21 Components	Type	Value
•		
Acetone (CAS 67-64-1)	STEL	500 ppm
	TWA	250 ppm
Butane (CAS 106-97-8)	STEL	1000 ppm
Canada. Ontario OELs. (Control o	of Exposure to Biological or Cl	hemical Agents)
Components	Туре	Value
Acetone (CAS 67-64-1)	STEL	750 ppm
	0.22	. 00 pp
	TWA	500 ppm
Butane (CAS 106-97-8)		• •
,	TWA TWA	500 ppm
Canada. Quebec OELs. (Ministry	TWA TWA	500 ppm 800 ppm
Canada. Quebec OELs. (Ministry Components	TWA TWA of Labor - Regulation Respect	500 ppm 800 ppm ting the Quality of the Work Environment)
Canada. Quebec OELs. (Ministry Components	TWA TWA of Labor - Regulation Respect Type	500 ppm 800 ppm ting the Quality of the Work Environment) Value
Canada. Quebec OELs. (Ministry Components	TWA TWA of Labor - Regulation Respect Type	500 ppm 800 ppm ting the Quality of the Work Environment) Value 2380 mg/m3
Butane (CAS 106-97-8)  Canada. Quebec OELs. (Ministry Components  Acetone (CAS 67-64-1)	TWA TWA  of Labor - Regulation Respect Type  STEL	500 ppm 800 ppm ting the Quality of the Work Environment) Value 2380 mg/m3 1000 ppm
Canada. Quebec OELs. (Ministry Components	TWA TWA  of Labor - Regulation Respect Type  STEL	500 ppm 800 ppm ting the Quality of the Work Environment) Value 2380 mg/m3 1000 ppm 1190 mg/m3
Canada. Quebec OELs. (Ministry Components  Acetone (CAS 67-64-1)	TWA TWA  of Labor - Regulation Respect Type  STEL  TWA	500 ppm 800 ppm ting the Quality of the Work Environment) Value 2380 mg/m3 1000 ppm 1190 mg/m3 500 ppm

Product name: SW248 FRESH TOTAL RELEASE BLAST OUT

SDS CANADA

1000 ppm

#### **Biological limit values**

**ACGIH Biological Exposure Indices** 

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove

supplier.

Other Wear suitable protective clothing.

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

**Appearance** 

Physical state Gas.
Form Aerosol.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

ng

132.89 °F (56.05 °C) estimated

range

Flash point -156.0 °F (-104.4 °C) Propellant estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

2.4 % estimated

(%)

Flammability limit - upper

12 % estimated

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure Not available.

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient (n-octanol/water)

Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

Specific gravity 0.7 estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability**Material is stable under normal conditions. **Possibility of hazardous**Hazardous polymerization does not occur.

reactions

**Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Nitrates. Fluorine. Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of exposure

**Inhalation** May cause drowsiness and dizziness. Headache. Nausea, vomiting.

**Skin contact** No adverse effects due to skin contact are expected.

**Eye contact** Causes serious eye irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision.

#### Information on toxicological effects

Acute toxicity Narcotic effects.

Acute toxicity	narcolic effects.	Narcotic effects.		
Components	Species	Test Results		
Acetone (CAS 67-64-1)				
<u>Acute</u>				
Dermal				
LD50	Guinea pig	> 7426 mg/kg, 24 Hours		
		> 9.4 ml/kg, 24 Hours		
	Rabbit	> 7426 mg/kg, 24 Hours		
		> 9.4 ml/kg, 24 Hours		
Inhalation				
LC50	Rat	55700 ppm, 3 Hours		
		132 mg/l, 3 Hours		
		50.1 mg/l		
Oral				
LD50	Rat	5800 mg/kg		
		2.2 ml/kg		
Butane (CAS 106-97-8)				
<u>Acute</u>				
Inhalation				
LC50	Mouse	1237 mg/l, 120 Minutes		
		52 %, 120 Minutes		

Components	Species	Test Results
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation

Not applicable.

Serious eye damage/eye

Causes serious eye irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

**ACGIH Carcinogens** 

Acetone (CAS 67-64-1) A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

ACETONE (CAS 67-64-1) Not classifiable as a human carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not likely, due to the form of the product.

#### 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components		Species	lest Results	
Acetone (CAS 67-64-1)				
Aquatic				
Crustacea	EC50	Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours	
Fish	LC50	Rainbow trout, donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours	

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

No data is available on the degradability of this product. Persistence and degradability

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24 Butane 2.89 Propane 2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

# 14. Transport information

**TDG** 

UN1950 **UN number** 

**UN proper shipping name** AEROSOLS, flammable

Transport hazard class(es)

Class 2.1 Subsidiary risk

Packing group Not applicable.

**Environmental hazards** 

Special precautions for user Not available.

This product meets the exemption requirements and may be shipped as a limited quantity.

IATA

**UN number** UN1950

Aerosols, flammable **UN proper shipping name** 

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** No. **ERG Code** 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

**IMDG** 

UN1950 **UN number UN** proper shipping name **AEROSOLS** 

Transport hazard class(es)

Class 2.1 Subsidiary risk Label(s) 2.1

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No. F-D. S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

# IATA; IMDG; TDG



# 15. Regulatory information

#### Canadian regulations

**Controlled Drugs and Substances Act** 

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

**Greenhouse Gases** 

Not listed.

**Precursor Control Regulations** 

Acetone (CAS 67-64-1) Class B

International regulations

Stockholm Convention

Not applicable.

**Rotterdam Convention** 

Not applicable.

**Kyoto protocol** 

Not applicable.

**Montreal Protocol** 

Not applicable.

**Basel Convention** 

Not applicable.

#### **International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Toxic Substances Control Act (TSCA) Inventory \*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

country(s).

### 16. Other Information

Issue date 06-13-2018

Version # 01

United States & Puerto Rico

Product name: SW248 FRESH TOTAL RELEASE BLAST OUT Product #: 1000014034 Version #: 01 Issue date: 06-13-2018 Yes

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Revision information** 

Product and Company Identification: Alternate Trade Names